



tSec Mini Reader



The tSec Mini reader provides a complete multi-technology smart card RFID solution. Compatible with all Wiegand capable control systems and incorporating RS-485 communication, ICT card readers allow rapid deployment of secure technology in any environment. Available in multiple card capabilities (13.56MHz, 125kHz and/or **Bluetooth®** wireless technology), with optional keypad and a choice of black or white, you can select the model to fit the needs and decor of any installation.

Feature Highlights

- > Multi card technology provides support for DESFire, MIFARE, and 125kHz cards from a single reader
- > Encrypted RS-485 or standard Wiegand connection
- > Bluetooth® / NFC credential reading
- > Supports OSDP communication protocol with secure channel
- > Read range up to 60mm (2.36") with proximity ISO cards
- > Configurable LED strip: 2 color control (blue and green) via external LED wiring, 16 color selectable for Protege function codes (RS-485 connection only)
- > Fully encapsulated design with environmental IP Rating of IP65 for outdoor and indoor operation
- > Small, discrete size
- > Optional Vandal Resistant Cover

Optional Features

A range of optional features means there is a model to suit everyone.

- > Choose from the 125kHz or MIFARE/DESFire models, or the Multi Technology model that supports all formats
 - > Optional Bluetooth® / NFC connectivity to allow access via a smartphone
 - > Optional vandal resistant cover
 - > Opt for either black or white according to your decor
-

Multi Card Technology

Available with 13.56MHz smart card capability or as a multi technology reader that combines both 125kHz proximity and 13.56MHz capabilities in a single unit, delivering maximum compatibility while providing a path forward to the latest technology. The multi technology reader is ideal for organizations that wish to transition to smart technology at their own pace, as it means they don't need to replace all their cards up front.

Optional Bluetooth® / NFC Credential Reading

Bluetooth® / NFC capability enables you to use your smartphone as your access credential for maximum convenience.

Equipped with support for most modern iOS and Android devices, you can unlock the door using a unique access credential that is entered against your user record in Protege, and authenticated by a secure cloud based server.

Convenient Programming

Reader configuration can be easily programmed for a wide range of functionality from any mobile device via the Protege Config App.

Flexible Communication

Choose between the intelligent RS-485 connection for fast, flexible, secure communication, or Wiegand for compatibility with all standard access control systems. RS-485 provides the added benefits of being easier and more cost effective to wire and deploy, and allows for direct integration with Protege systems, enabling you to make changes on the fly once readers are installed. RS-485 also allows for longer cable runs and offers a simpler firmware update process.

OSDP 2.2 Communication

The OSDP protocol improves interoperability and adds scalability, flexibility and ease of implementation.

OSDP with secure channel offers additional security with AES-128 encryption and predefined key management and authentication.

For more information, see [Application Note 321: Configuring ICT Readers for OSDP Communication](#), available from the ICT website.

Configurable LED Strip

The card reader provides the ability to change the color of the LED strip (16 colors available) to show when a function has started, succeeded or failed. For example, for a function that is used to arm an area you might set the LED to change to orange to show that the function has started, yellow to show that the area has armed successfully, and red to indicate when the function has failed.

*This feature is only supported when wired using RS-485.

IP65 Protection

The IP65 environmental rating provides a high degree of protection from the elements, making the reader suitable for harsh environments. Readers can be mounted indoors or outdoors, located anywhere from the car park gate to the office door.

Optional Vandal Resistant Cover

Designed to withstand some of the harshest settings, the optional vandal resistant covers are ideal for locations where a card reader may be exposed to damage, including corridors, parking buildings, correctional facilities, and other public places. Highly resistant to impact, such as from the swing of a hammer or baseball bat, its robust construction provides greater durability and protection against vandalism and malicious damage. The flush design also serves as an anti-ligature measure for an additional level of safety.



Covers can be ordered using the following part codes:

- > **tSec Standard Reader:** PRX-SVRC
- > **tSec Extra Reader:** PRX-XVRC
- > **tSec Mini Reader:** PRX-MVRC

Mounted correctly, the card reader vandal resistant cover is compliant to DHF TS 001:2013, the ENHANCED REQUIREMENTS & TEST METHODS FOR ANTI-LIGATURE HARDWARE to grade B4 for vertical direction devices and to impact level IK10.

Keypad Support

Regular keypad variations of the tSec reader range do not operate correctly with the vandal resistant covers that are provided separately. You must order the reader as a kit (including the cover) using one of the following part codes:

- > **tSec Standard Reader:** PRX-TSEC-STD-KP-VRC (Multi Technology), PRX-TSEC-STD-DF-KP-VRC (13.56MHz), PRX-TSEC-STD-KP-BT-B-VRC (Multi Technology with Bluetooth® Wireless Technology).
- > **tSec Extra Reader:** PRX-TSEC-EXTRA-KP-VRC (Multi Technology), PRX-TSEC-EXTRA-DF-KP-VRC (13.56MHz), PRX-TSEC-EXTRA-KP-BT-B-VRC (Multi Technology with Bluetooth® Wireless Technology).

Available Models / Ordering Information

The tSec Mini reader is available with a range of features.

Mini	85 x 46 x 17mm (3.35 x 1.81 x 0.67")				
	Keypad	125kHz	MIFARE/ DESFire/ NFC	Bluetooth® Technology	Vandal Resistant Cover*
PRX-TSEC-MINI-B tSec Mini Multi-Technology Card Reader		✓	✓		
PRX-TSEC-MINI-125-B tSec Mini 125kHz Card Reader		✓			
PRX-TSEC-MINI-DF-B tSec Mini 13.56MHz Card Reader			✓		
PRX-TSEC-MINI-BT-B PRX-TSEC-MINI-BT-W tSec Mini Multi-Technology Card Reader with Bluetooth® Wireless Technology		✓	✓	✓	
PRX-TSEC-MINI-DF-BT-B tSec Mini 13.56MHz Card Reader with Bluetooth® Wireless Technology			✓	✓	

* Keypad editions with vandal resistant cover included. Covers may be purchased separately for readers without keypads, but regular keypad editions do not support vandal resistant covers.

Technical Specifications

Ordering Information	
Order Codes	See Reader Editions.
Power Supply	
Operating Voltage	12VDC (9.5 to 14VDC)
Operating Current	Standard Reader: 254mA (Peak, Reading) Extra Reader: 298mA (Peak, Reading) Mini Reader: 203mA (Peak, Reading)
Communications	
Card Read Range	MIFARE 60mm (2.36") * DESFire EV1 ISO 15mm (0.6") * 125kHz Clamshell 40mm (1.57") †
Tag Read Range	MIFARE 30mm (1.2") * DESFire EV1 6mm (0.23") * 125kHz 25mm (0.98") †
Wiegand Interface	Multiple format 26 or 34 Bit data 0 and data 1, card defined
Frequency	13.56 MHz ISO/IEC 14443 Type A * 125KHz pulse width modulated †
Multi Conductor Cable	Wiegand: 22Awg alpha 5196, 5198, 18Awg alpha 5386, 5388. Max Distance 150m (492ft) Module comms/RS485: Belden 9842 or equivalent. Max distance 900m (3000ft)
OSDP Communication	OSDP standard 2.2 with Secure Channel Protocol ** / ***
Bluetooth® Wireless Technology	
Bluetooth® Read Range	Proximity mode: up to 0.5m (1.6ft) Configurable ** Action unlock (shake): up to 5m (16.4ft) Configurable **
Bluetooth® Electronic Credential Transmission Technology	NRF8001 Bluetooth® version 4.0 compliant Proprietary data exchange protocol. AES128 Encrypted Reader App Version: 1.04.175 and above Credentials can be distinguished by unique site code and card number
Bluetooth® Wireless Device	Protege Mobile 1.0.x
NFC	
NFC Read Range	Up to 60mm ***
NFC (Near-field communication) electronic credential transmission technology	Android 4.4 or above, with phones which support ISO7816-4 Proprietary Secured DESFire credential Credential is AES-256 (NIST certified AES algorithm) Reader App Version: 1.04.175 and above Credentials can be distinguished by unique site code and card number
NFC Wireless Device	Protege Mobile 1.0.x
Operating Conditions	
Environment IP Rating	IP65
Operating Temperature	UL/ULC -35° to 66°C (-31° to 151°F) : EU EN -40° to 70°C (-40° to 158°F)
Storage Temperature	-10° to 85° C (14° to 185° F)
Mean Time Between Failures (MTBF)	520,834 hours (calculated using RFD 2000 (UTE C 80-810) Standard)
Dimensions	

Reader Dimensions (H x W x D)	Standard Reader: 117 x 46 x 18mm (4.61 x 1.81 x 0.71") Extra Reader: 117 x 75 x 18mm (4.61 x 2.95 x 0.71") Mini Reader: 85 x 46 x 17mm (3.35 x 1.81 x 0.67")	
Vandal Resistant Cover (H x W x D)	PRX-SVRC Standard Reader Cover: 162 x 91 x 22.6mm (6.37 x 3.58 x 0.88") PRX-XVRC Extra Reader Cover: 162 x 120 x 22.6mm (6.37 x 4.72 x 0.88") PRX-MVRC Mini Reader Cover: 127 x 88 x 20mm (5.0 x 3.46 x 0.78")	
Reader with Surface Mount Box (H x W x D)	Standard Reader: 117 x 46 x 51mm (4.61 x 1.81 x 2.00") Extra Reader: 119 x 77 x 52mm (4.69 x 3.05 x 2.05")	
Reader Weights	Net Weight	Gross Weight
Standard Reader	110g (3.9oz)	130g (4.6oz)
Standard Reader with Vandal Resistant Cover	190g (6.7oz)	280g (9.9oz)
Extra Reader	160g (5.6oz)	190g (6.7oz)
Extra Reader with Vandal Resistant Cover	270g (9.5oz)	360g (12.7oz)
Mini Reader	80g (2.8oz)	100g (3.5oz)
Standard Reader Surface Mount Box	40g (1.4oz)	60g (2.1oz)
Extra Reader Surface Mount Box	70g (2.5oz)	100g (3.5oz)

* Applies to MIFARE/DESFire and Multi-Technology models only

† Applies to 125kHz and Multi-Technology models only

** Applies to Bluetooth® wireless technology enabled models only

*** Applies to NFC capable models only

The size of conductor used for the supply of power to the unit should be adequate to prevent voltage drop at the terminals of no more than 5% of the rated supply voltage.

The **Bluetooth®** word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Integrated Control Technology is under license. Other trademarks and trade names are those of their respective owners.

Regulatory Notices

New Zealand (RSM) and Australia (RCM)

This equipment carries the R-NZ label and complies with EMC and radio communications regulations of the Australian Communications and Media Authority (ACMA) governing the Australian and New Zealand (AS/NZ) communities.

AS/NZS 2201.1 Class 5

Protege systems conform to AS/NZS 2201.1:2007 Class 5 intruder alarm systems standards for the construction, operation, performance and installation of intruder alarm equipment and systems installed in clients' premises.

CE - Compliance with European Union (EU)

Conforms where applicable to European Union (EU) Low Voltage Directive (LVD) 2014/35/EU, Electromagnetic Compatibility (EMC) Directive 2014/30/EU, Radio Equipment Directive (RED) 2014/53/EU and RoHS Recast (RoHS2) Directive: 2011/65/EU + Amendment Directive (EU) 2015/863.

This equipment complies with the rules of the Official Journal of the European Union, for governing the Self Declaration of the CE Marking for the European Union as specified in the above directives.

Security Grade 4, Environmental Class II, EN 50131-1:2006+A2:2017, EN 50131-3:2009, EN 50131-6:2008+A1:2014, EN 50131-10:2014, EN 50136-1:2012, EN 50136-2:2013, EN 60839-11-1:2013, Power frequency magnetic field immunity tests EN 61000-4-8, Readers Environmental Class: IVA, IK07.

UK Conformity Assessment (UKCA) Mark

This equipment carries the UKCA label and complies with all applicable standards.

UL/ULC (Underwriters Laboratories)

- > UL 294 for Access Control System Units
- > CAN/ULC S319 for Electronic Access Control Systems

Industry Canada

ICES-003

This is a Class A digital device that meets all requirements of the Canadian Interference-Causing Equipment Regulations. Cet appareil numérique de la classe A est conforme à la norme NMB-003 du Canada.

CAN ICES-3 (A)/NMB-3(A)

Federal Communications Commission (FCC)

FCC Rules and Regulations CFR 47, Part 15, Class A.

This equipment complies with the limits for a Class A digital device, pursuant to Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference; (2) This device must accept any interference received, including interference that may cause undesired operation.

Open Supervised Device Protocol (OSDP) Verified Logo

This equipment carries the OSDP Verified logo which indicates that this device is compliant with the OSDP 2.2 PD Secure profile and all applicable standards.

- > For a full regulatory and approval list please visit the ICT website.

Designers & manufacturers of integrated electronic access control, security and automation products.
Designed & manufactured by Integrated Control Technology Ltd.
Copyright © Integrated Control Technology Limited 2003-2022. All rights reserved.

Disclaimer: Whilst every effort has been made to ensure accuracy in the representation of this product, neither Integrated Control Technology Ltd nor its employees shall be liable under any circumstances to any party in respect of decisions or actions they may make as a result of using this information. In accordance with the ICT policy of enhanced development, design and specifications are subject to change without notice.

www.ict.co

17-Jun-22